ntercom®

TECHNICAL DATA SHEET

ECOSTICK® 9004

Description/Nature of the product: Aqueous adhesive based on modified natural rubber latex

<u>Characteristics:</u> Ideal for coupling and folding leather, eco-leather, fabrics, covers, cardboards, for

producing belts, uppers, bags, wallets, heels, orthopedic insoles and for

assembling insoles.

Specifications: Water based adhesive, does not leave spots, does not stiffen the leather and

does not gum the needle in the seam. It is stabilized for spraying application. High tack on the surfaces, perfect hold on leather and synthetics. Quick drying and long open time. It can be used together with poly-chloroprene solvent based

adhesives. Non toxic, non inflammable, non harmful.

Instructions for use: Apply the adhesive on both sides. Let it dry until the film of adhesive becomes

transparent. Couple and press.

Remarks for use:

Chemical and physical characteristics:

Application by: Spray gun, sponge, brush

Quantity to be applied approx.: 50 g/m2 - 150 g/m2 Depends on how absorbing the bonded substrates are

Open time: Several hours

Working temperature: Room temperature, not below 16° C.

Catalyst:

Mixing ratio:

Pot-life:

Dilution: Do not dilute it

Cleaning of tools: Water. For removing dried adhesive residues, use ISA-VERDUNNER 111 or 220.

Solid content approx. 56 \pm 1,00

Density approx. ca.0,98 g/cm3 at 20° C \pm 0,02

Ph approx. $9 \pm 1,00$

Colour: White

Viscosity approx. 4000 (brookfield, spindle4, 30RPM) \pm 500,00

Expiring from production (months) 9

Behaviour in cold: Product is permanently damaged at temperatures below + 5°C

Flashpoint: Not applicable





ECOSTICK® 9004

Storing conditions:

Store the sealed cans/containers in an adequate place, recommended storage temperature is not below 5°C and not above 30°C. The ideal storing condition is at a cool place and at room temperature (23°C). Protect from direct sun light.

The given information we believe is correct according to the best of our knowledge and tests. The recommendations and suggestions made herein as generally it is in any written or verbal advice or testing, are made without guarantee. In every case we urge and recommend that purchasers, before using any product, make their own tests to determine, to their own satisfaction, its suitability for their particular purpose according to their own operating conditions. The suitability of a product for an intended use shall be solely up to the user. The user accepts the products "as it is" and without warranties, expressed or implied. Warranties are given only as for our conditions of sale and delivery. Nothing contained herein is to be understood as permission or recommendation to practise a patented invention without a licence, and the purchaser should determine whether relevant patents exist.

INTERCOM SRL Printing Date: 02.02.2016

Via della Gora 13 50025 Montespertoli - Florence - Italy Tel.+39 0571 671096 Fax: +39 0571 671151