# ntercom®

#### TECHNICAL DATA SHEET

## **ECOSTICK® 9015ST**

**<u>Description/Nature of the product:</u>** Modified poly-chloroprene latex, 50% c.a in water.

<u>Characteristics:</u> Ideal for coupling and folding leather, eco-leather, fabrics, covers, cardboards, for

producing belts, uppers, bags, wallets, heels, orthopedic insoles and for

assembling insoles.

**Specifications:** Water based adhesive, does not leave spots, does not stiffen the leather and

does not gum the needle in the seam. It is stabilized for spraying application. High tack on the surfaces, perfect hold on leather and synthetics. Quick drying and long open time. It can be used together with poly-chloroprene solvent based

adhesives. Non toxic, non inflammable, non harmful.

<u>Instructions for use:</u> When applied on one side, couple and press while the glue is still wet. When

applied on both sides, coupling can be done immediately, either after 3 minutes or

up to several hours.

**Remarks for use:** If the open time is exceeded, bonding can be made after having warmed up at

60°C the material to bond.

### **Chemical and physical characteristics:**

Application by: Spray gun, roller machine

Quantity to be applied approx.: 50 g/m2 - 150 g/m2. Depends on how absorbing the bonded substrates are

Open time: Up to 2-4 hours, depending on the amount of adhesive used and on the kind of

support.

Working temperature: Room temperature, not below 16° C.

Catalyst:

Mixing ratio:

Pot-life:

Dilution: Demineralised water

Cleaning of tools: Water. For removing dried adhesive residues, use ISA-VERDUNNER 111 or 220.

Solid content approx. 50  $\pm$  1,00

Density approx. ca.1 g/cm3 at  $20^{\circ}$ C  $\pm$  0,02

Ph approx.  $9 \pm 1,00$ 

Colour: White

Viscosity approx. 1200(brookfield, spindle4, 50RPM)  $\pm 400,00$ 

Expiring from production (months) 12

Behaviour in cold: Product is permanently damaged at temperatures below + 5°C

Flashpoint: Not applicable





## **ECOSTICK® 9015ST**

#### **Storing conditions:**

Store the sealed cans/containers in an adequate place, recommended storage temperature is not below 5°C and not above 30°C. The ideal storing condition is at a cool place and at room temperature (23°C). Protect from direct sun light.

The given information we believe is correct according to the best of our knowledge and tests. The recommendations and suggestions made herein as generally it is in any written or verbal advice or testing, are made without guarantee. In every case we urge and recommend that purchasers, before using any product, make their own tests to determine, to their own satisfaction, its suitability for their particular purpose according to their own operating conditions. The suitability of a product for an intended use shall be solely up to the user. The user accepts the products "as it is" and without warranties, expressed or implied. Warranties are given only as for our conditions of sale and delivery. Nothing contained herein is to be understood as permission or recommendation to practise a patented invention without a licence, and the purchaser should determine whether relevant patents exist.

INTERCOM SRL Printing Date: 21.09.2016

Via della Gora 13 50025 Montespertoli - Florence - Italy Tel.+39 0571 671096 Fax: +39 0571 671151