



## Global LP 8970i Series

### HIGH SPEED POSTBED MACHINES

#### LP 8971 I-AUT

High speed, single needle postbed machine, driven by Ho Hsing built-in mini servo motor and integrated control box in the sewing head, with top driven roller, wheel- and needle feed and standard hook.

Machine equipped with thread trimming device, automatic back tack and presser foot lift (all electric).

#### LP 8974 I-AUT

Double needle postbed machine, driven by Ho Hsing built-in mini servo motor and integrated control box in the sewing head, with wheel feed and top driven roller presser (no needle feed) and equipped with standard hooks, thread trimming device, automatic back tack and presser foot lift (all electric). Standard needle gauge 2,0 mm.

### TECHNICAL SPECIFICATIONS

**MACHINE SPEED**  
max 2500 spm

**OILING SYSTEM**  
Fully automatic

**FEED TYPE**  
needle and wheel feed  
top driven roller presser

No needle feed on the  
LP 8994

**STITCH LENGTH**  
max 7 mm

**PRESSER FOOT LIFT**  
max: 14 mm (electric)

**NEEDLE TYPE**  
134 LR

**DOUBLE NEEDLE TYPE**  
Optional gauges:  
1,8 mm, 2,2 mm, 2,4 mm