

Spraying system S8 + tank CO installed

Item Card : I088

Device equipped with spray gun G6 designed for both precisig or larger gluing. In particular it can spray from a minimum of 3 mm up to a maximum cone shaped jet of 50 mm. The spray gun is held up by an equalizer for making it easy to handle. It can be set going manually by pressing a lever or through a pedal so to leave the operator's hands free. The spray gun is fed by a stainless steel tank 10 lt capacity.



All the spray gun functions can be adjusted: quantity of adhesive, width of jet and quality of distribution. Combined with the vacuum benches it allows to reduce the application times while guaranteeing a perfect adhesive distribution even on different thicknesses. A jet of air immediately before and after the adhesive nebulisation keeps the nozzle constantly clean. The absolute precision, the high versatility and the maintenance free make our spray systems suitable for many range of bondings in big and small production plants. The tank is conceived in a way that allow the use of the adhesive in bag in box avoiding to make dirty the tank and to filter the glue thus preventing the contact with air which can alter its properties.

Specifications:

09.07.2015

Portata m3/h :	Volt :	Prevalenza:	Aria lt/min :	30	Bar esercizio :	6
Decibel (dB) :	Watt :	Hertz :	Ampere :		Consumo medio :	
Gross weight kg: 13,850	Tare:	Lenght mt: 0,51	Height mt: 0,82		Volume m3: 0,11	
Net Weight kg: 13,850	Packaging:	Width mt: 0,26	Usable Depth, cm:		X	