

Intercom S.R.L.

Sede Legale e Operativa Via della Gora, 13 50025 Montespertoli FI

50025 Montespertoli FI Cod.Fisc. - P.Iva 06183210480 - REA 607410 info@intercomsas.it www.intercomsas.it Cap.sociale € 50.000 int.vers.

Cap.sociale € 50.000 int.vers. Tel. +39 0571 671096 - Fax +39 0571 671151

Vacuum bench B7 spraying system S8 and tank CO assembled and installed

Item Card: I788

The machine is composed by: -Vacuum bench created to absorb even more the nebulized adhesive, equipped with a silent and powerful engine. -Spray gun G6 designed for both precise and large areas bonding. In particular it is possible to spray the glue from a minimum of 3 mm up to a maximum of 50 mm. -Stainless steel tank 10 lt. capacity, treated with non-stick Teflon.

Vacuum bench, with wheels for easy displacement inside the factory. The bench can be connected to other modules so as to increase the working surface while meeting the requirements of clients producing big sized items. The spray gun is held up by an equalizer for making it easy to handle. It can be operated manually by pressing a lever or through a pedal to leave the operator's hands free.



The operator, after starting the machine, can place the materials on the working plane so to make maximum use of the intake on the working plane for both keeping the materials standing and absorbing the nebulized adhesive. All the spray gun functions can be adjusted: quantity of adhesive, width of jet and quality of distribution even on different thicknesses. For a proper functioning of the vacuum bench it is recommended to replace the filter each time is visibly dirty or when the vacuum bench is not intaking properly. To speed up the working process it is possible to use some nets in order to reduce the idle time due to loading and unloading the pieces on the working area. A jet of air immediately before and after the adhesive nebulization keeps the nozzle constantly clean. Our systems are maintenance free. The tank is conceived in a way that allow the use of the adhesive in bag in box avoiding to make dirty the tank and to filter the glue thus preventing the contact with air which can alter its properties.

Specifications:

31.03.2017

Net Weight kg:	142,000	Packaging:		Width mt:	0,80	Usable Depth, cm:		87 X 70	
Gross weight kg:	145,000	Tare:	3,000	Lenght mt:	1,20	Height mt:	1,94	Volume m3:	1,86
Decibel (dB):	72/67	Watt:	245	Hertz :	50/60	Ampere :	2,6	Average Consumpt	on: 245
M3/h :	2400	Voltage:	230	Pa:	270	Air lt/min :	30	Bar:	6